

編織銅帶 COPPER BRAID WARP



編織銅帶 + P V C 被覆

斷面積	導體構造		寬度×厚度	導體電阻		備 註
CROSS SECTION AREA mm ²	CONSTRUCTION		DIMENSION WIDE x THICKNESS (mm x mm)	CONDUCTOR RESISTANCE 20℃Ω /km		
	線 徑	條 數		裸 銅	鍍 錫	
	COPPER WIRE DIAMETER (mm)	NO. OF CONDUCTOR (pcs)		BC	TC	
0.55	0.12	48	2.00 x 0.70	38.85	40.95	
0.73	0.12	64	2.30 x 0.75	29.13	30.72	
0.90	0.12	80	2.90 x 0.80	23.32	24.15	
1.10	0.12	96	2.90 x 0.90	19.43	20.48	
1.30	0.12	112	3.30 x 0.90	16.65	17.60	
1.50	0.12	128	3.30 x 1.10	14.57	15.36	
1.85	0.12	160	4.15 x 1.10	13.18	13.89	
1.40	0.12	120	3.80 x 0.80	15.50	16.38	
1.70	0.12	144	4.30 x 1.00	14.65	15.35	
1.90	0.12	168	5.00 x 1.20	12.55	13.22	
2.20	0.12	192	5.25 x 1.30	10.98	11.58	
2.75	0.12	240	5.70 x 1.30	8.79	9.26	
3.30	0.12	288	10.0 x 1.00	7.32	7.72	
3.90	0.12	336	11.1 x 1.10	6.28	6.62	
9.40	0.12	816	17.4 x 1.45	2.86	2.95	
9.80	0.12	864	18.5 x 1.50	2.64	2.79	
9.80	0.16	480	18.1 x 1.80	2.68	2.82	
14.00	0.18	576	20.0 x 2.00	1.50	1.58	
22.00	0.18	912	25.0 x 2.50	0.95	1.01	
38.00	0.18	1536	35.0 x 3.20	0.65	0.7	
50.00	0.18	1968	40.0 x 3.50	0.35	0.4	